












ELECTRONIC BATTERY MAIN SWITCH & CONTROL SWITCHES

PRODUCT RANGE







S220 SERIES

- 200 Amps rated, 24V or 12V
 - Applications: agriculture, trucks, special vehicles...
 - Bistable actuator
 - Power connections M8
 - Cable output for any type of connector
 - up to 2 inputs & 1 output
 - Monostable relay variant
 - Optional Busbar for power distribution



S250 SERIES




- **300** Amps rated, 24V or 12V
 - Applications: trucks, agriculture, marine...
 - Bistable actuator
 - Power connections M10
 - Cable output for any type of connector
 - up to 5 inputs & 3 outputs
 - ADR variant
 - 2-pole SLP variant (UK) with Slave Unit










- **300** Amps rated, 24V or 12V
 - Applications: trucks, busses, agriculture...
 - Bistable actuator
 - Power connections M10
 - Cable output for any type of connector
 - up to 5 inputs & 3 outputs
 - ADR variant
 - Optional manual control









S270 SERIES

300 Amps rated, 24V


- Dual battery management
- Applications: trucks, hybrid vehicles...
- Bistable actuator
- Power connections M10
- Cable output for any type of connector
- up to 2 inputs & 2 outputs
- ADR homologation
- Relay variant












S280 SERIES

Dual circuit 24V / 12V

- **300A / 50A rated**
- Applications: trucks, busses
- Bistable actuators
- Power connections M10 & M6
- Cable output for any type of connector
- up to 3 inputs & 3 outputs
- Tachograph supply output
- ADR variant
- SLP variant (UK) with Slave Unit S270
- Optional chassis control switch (HDSCS connector)








S310 SERIES

- **300** Amps rated, 24V
 - Applications: trucks, busses...
 - Bistable actuator
 - Power connections M10
 - Cable output for any type of connector
 - up to 5 inputs & 3 outputs
 - **ADR** variant









S255 SERIES

- 2-pole, 300 Amps rated, 24V or 12V
 - Applications: trucks, mine vehicles, road trains...
 - Bistable actuators
 - Power connections M10
 - **2x** 7-pole DIN connectors
 - up to 3 inputs & 2 outputs
 - **External rollover sensor control**
 - **ADR**









S355 SERIES

- 2-pole, 300 500 Amps rated
 - Applications: trucks, mine vehicles, road trains...
 - Automatic 12V / 24V range
 - Bistable actuators
 - Power connections M10 or M12
 - **HDSCS connector (variant with 2x 7-pole DIN connectors)**
 - up to 3 inputs & 2 outputs
 - Variant with manual override control
 - Changeover switch variant
 - ADR variant with integrated rollover sensor





PUSHBUTTON





- Momentary action, 1 pole, 10 Amps
 - 2-pin bayonet connector DIN 72585 / ISO 15170
 - Normally Open (NO) circuit
 - or Normally Closed (NC) circuit
 - Variant with pigtail and Superseal connector (other type on request)
 - Different button colour and symbol options









ROTARY SWITCH





- 2-position switch, 1 pole or 2 poles, 10 Amps
 - 2-pin or 4-pin bayonet connector DIN 72585 / ISO 15170
 - 1 or 2 Normally Open (NO) circuits
 - or 1 Normally Open (NO) & 1 Normally Closed (NC) circuits
 - Variant with protective lid (ADR applications)
 - Variant with lockable lid in OFF position
 - Variant with pigtail and HDSCS or Superseal connector (other type on request)
 - Different colour and symbol options







